




## Engineering Submittal Form – MA-6F4

**CERTIFIED FOR:**

Job Name:	Customer Name:
Location:	Customer P.O.:

**Recommended Usage:**

Use as a free standing; non-penetrating support stand for Single or Multiple runs of piping, conduit, duct, refrigeration lines, solar panels, cable trays and equipment supports. Accepts industry standard accessories.



**Standard Composition:**

Extruded Aluminum with integrated 1 5/8" shallow strut, Solid flat base with rolled edges. Available lengths pre-cut up to 10'. 100% recyclable material. Made in USA.

*MAPA Products Supports are designed and manufactured in accordance with MSS SP-58-2002 and MSS SP-69-2002. Refer to MAPA Products "Recommended Installation Guidelines" for standard installation and spacing recommendations.*

**Composition:**

Extruded Aluminum w/ Integrated 1 5/8" shallow strut  
 Strut Length 6"  
 Base Dimensions 5" X 6"  
 Footprint 30 sq in.  
 Load Factor 5 PSI

**Optional Accessories:**

- Add Suffix "P" .125 neoprene pad.
- MWP914- 1/2" thick rubber walk pad
- Snap-N-Strut Clamps (Refer to SNS selection chart for sizing)

**Certification Data**

Support Pad Options							
QTY	NP	P	WP	SNS Selection	Pipe Size	Service	Notes & Options
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				

<b>DRAW N</b>				<b>CHECKED</b>		<b>DATE</b>	<b>DWG.NO.</b>
							<b>Doc. #: M-13808</b>