



## Engineering Submittal Form – MT-1V

**CERTIFIED FOR:**

Job Name:	Customer Name:
Location:	Customer P.O.:

**Recommended Usage:**

Use as a pipe support stand for single piping runs installed on single ply and built-up roofs where thermal expansion is not a concern.

**Standard Composition:**

Support Base is injection molded 33% Fiberglass Reinforced 6/6 Nylon with highly dispersed carbon black providing weathering resistance and UV stabilization.



*MAPA Products Supports are designed and manufactured in accordance with MSS SP-58-2002 and MSS SP-69-2002.*

*Refer to MAPA Products "Recommended Installation Guidelines" for standard installation and spacing recommendations.*

Nylon Based Single Post Support Models	Maximum Load	Base Dimension	Assembly	Maximum Adjustability
MT-1V	75 lbs	6"x 6"	Pipe Cradle for 1 1/2" OD	Fixed Height 4"

**Optional:** (See Accessories in Catalog and specify desired model.)

- Add Suffix "P" .125 neoprene pad.
- Add *MWP1010* – 1/2" Walk Pad
- MPS-7 SS Pipe Strap

**Warranty:**

**ISIMET / MAPA, LLC** will repair or replace any defective parts or workmanship of this product for a period of three years from date of delivery. Rusting that is not detrimental to the integrity of the support is not warranted. Damage caused by incorrect installation, alteration or improper usage is not warranted. Recovery rights shall be limited to the total sum of the amounts paid for the product by the purchaser.

**Limits of Liability:**

**ISIMET / MAPA, LLC** liability shall be limited to costs of repair or replacement parts. Supports are not intended for usage other than those expressly described in this brochure. **ISIMET / MAPA, LLC** shall not be liable for damage or injury caused by the improper use of the product.

Certification Data								
Support Pad Options								
QTY	NP	P	WP	Pipe Strap	Pipe Size	Pipe Type	Service	Notes & Options

<b>DRAWN</b>	<b>CHECKED</b>	<b>DATE</b>	<b>DWG.NO.</b>

*Doc. #: M-13702*