



Certified For: _____
Job Name: _____
Location: _____
Customer PO: _____
Model Number: _____



MPX– Utility Pedestal

Composition:

- Pedestal – 2” X 2” 16 gauge 304 Stainless Square Tubing
- Total length indicated by suffix xx + yy
- Solid welded stainless cap tops off the Shroud.
- Under deck Flange – Welded 16 gauge sheet metal – black painted W/ anchor bolts and trim to secure pedestal to roof structure.

Practical Application: The MAPA Products Rainproof Utility Pedestal Switch provides a means to mount a variety of services for local applications. The Stainless Shroud with integrally welded deck flange enables a

Features: The standard Stainless Steel Shroud extends above roof line thirty-six inches with an additional twelve inches of shroud beneath roofline so as to permit the unit to be securely fastened to the roof structural member by securing the under-deck mounting flange to a welded deck flange. The roof flange is provided with fastening hardware to enable the installer to secure the flange first against the shroud and positive weather-tight flash of the unit to the roof membrane without the need for additional flashing or pitch-pan.

Series and Model Specifics:

Disconnect Models

Model	Description
MPX2:36/12	Utility Pedestal 2” Less Disconnect
MPX-20-G:36/12	36” Utility Pedestal w/ GFCI
MPX-20-GL:36/12	36” Utility Pedestal w/ GFCI and Incandescent light array
MPX-20-GL-S:36/12	36” Utility Pedestal w/ GFCI, Incandescent light array and switch
MPX-20-L:36/12	36” Utility Pedestal w/ Incandescent light array
MPX-20-L-S:36/12	36” Utility Pedestal w/ Incandescent light array and switch

Model MPX-20 Utility Pedestals are max rated 20 amps.

Model Number: _____

Available Options:

D	Upper Deck Cap
---	----------------

xx/yy	Extended Lengths Above & Below the flange. Specify Actual Dimensions:
-------	---

SA	Structurally Attached - per the approval of Florida Product Approval FL-21083
----	---

Y	Yard Installation
---	-------------------

Custom configurations are available to meet specific design criteria. Contact the manufacturer.

Note: Pedestals are custom fabricated for specific project requirements and typically require a four (4) week lead-time after product submittal approval.

Warranty:

Limited Lifetime Warranty--When installed in accordance with MAPA installation and maintenance specifications and using only MAPA materials, MAPA warrants its support bases and assemblies to be free from defect and will repair or replace product at MAPA's discretion. Rusting that is not detrimental to the integrity of the support is not warranted. Damage caused by incorrect installation, improper usage or improper maintenance is not warranted. Recovery rights shall be limited to the total sum of the amounts paid for the product by the purchaser.

Limits of Liability:

ISIMET/MAPA liability shall be limited to costs of repair or replacement parts. Supports are not intended for usage other than those expressly described in product catalog. ISIMET/MAPA does not perform engineering design and shall not be liable for damage or injury caused by the improper use or installation of the product.

MAPA Products, LLC.
103 C J Wise, Naples, TX 75568
MAPA: 903-781-6996
customerservice@mapaproducts.com

Doc #: M-13403

Effective Date: January 2020