

CERTIFIED FOR:	
JOB NAME:	
LOCATION:	
CUSTOMER:	
CUSTOMER P.O.:	

Submittal Information: MPH-24FP:24/9 Pedestal Hydrant

Shown below with deck flange and deck cap.



Composition:

- Black painted cast aluminum Weather-Guard Dome Handle
- Available with Steel Grey Powder Coat finish or Grade 304
- stainless steel shroud w/ seamlessly welded flange
 ¾" inlet / Max. 125 psi / ¾" Male Hose Fitting with Built-in Vacuum Breaker
- Stainless steel operating rod and reservoir

Insulation:

• R-8 rated / Thermo-Cell insulation

Mounting Hardware:

• Black painted under-deck support flange w/ hardware

Options:

Suffix "D" – Deck Cap Suffix: xx/yy – Max 72" Extended shroud for above or below roofline | 6" increments

Practical Application

Where there is concern for potential damage to the hydrant assembly due to severe cold weather, the MPH-24FP Pedestal Hydrant with its Weather-Guard Dome provides a freeze proof hose station at required locations. The Grey Powder Coat or Stainless-Steel Shroud and Base allow the contractor to make a positive, weather tight flashing to the hydrant in rooftop applications. The integrated vacuum breaker allows the hydrant to meet ASSE 1057 Sanitary Yard Hydrant Standard.

Features

- The Weather-Guard Domed Handle enables the user to operate the valve assembly while preventing moisture from entering the assembly when the valve is in the OFF position.
- Durable Stainless Steel or Grey Powder Coat shroud resists motion that could disturb watertight installation.
- Stainless steel reservoir installed within the buildings conditioned area.
- The Under-deck Flange prevents the Hydrant from becoming dislodged from the roof membrane during operation.

CERTIFICATION DATA								
	STYLE		Composition		Deck	Extended	Dimensions	Notes
QUANTITY	Roo	f/Yard	SS	PC	Сар	Length (Max. 72")	(Standard is 24" above / 9" below)	

	HECKED	DATE	DWG.NO.
--	--------	------	---------