



CERTIFIED FOR: _____
 JOB NAME _____
 LOCATION _____
 CUSTOMER _____
 CUSTOMER P.O. _____

Submittal Information: MPH-24D:24/9 Pedestal Hydrant

Composition:

- Black painted cast aluminum Weather-Guard Dome Handle
- Grade 304 stainless steel shroud w/ welded stainless steel flange
- Male Hose Fitting / Vacuum Breaker



Mounting Hardware

- Black painted under-deck support flange w/ hardware

Features:

- The Auto-Drain port will discharge the water remaining in the standpipe to an open-site drain.
- The Hydrant utilizes a bronze full port auto drain ball valve within the stainless steel shroud.
- The Under-deck Flange prevents the Hydrant from becoming dislodged from the roof membrane during operation.
- The Weather-Guard Domed Handle prevents moisture from entering the assembly when the valve is in the OFF position.
- Provided with "loose fit" wye strainer for field installation.

Options:

- Deck Cap – Suffix "D"
- Suffix: xx/yy – Extended shroud for above or below roofline – 6" increments

Practical Application

Where there is concern for potential damage to the hydrant assembly due to severe cold weather, the MPH-24D:24/9 Pedestal Hydrant with its Weather-Guard Dome provides a freeze proof hose station at required locations. The Auto-Drain port is located below the freeze line at the base of the hydrant. The Stainless Steel Shroud and Base allow the contractor to make a positive, weather tight flashing to the hydrant in rooftop applications.

Warranty:

Limited Lifetime Warranty--When installed in accordance with MAPA installation and maintenance specifications and using only MAPA materials, MAPA warrants its support bases and assemblies to be free from defect and will repair or replace product at MAPA's discretion. Rusting that is not detrimental to the integrity of the support is not warranted. Damage caused by incorrect installation, improper usage or improper maintenance is not warranted. Recovery rights shall be limited to the total sum of the amounts paid for the product by the purchaser.

Limits of Liability:

ISIMET/MAPA liability shall be limited to costs of repair or replacement parts. Supports are not intended for usage other than those expressly described in product catalog. ISIMET/MAPA does not perform engineering design and shall not be liable for damage or injury caused by the improper use or installation of the product.

CERTIFICATION DATA

QUANTITY	Style Roof/Yard	Deck Cap	Dimensions <i>(If other than Standard 24" above roofline)</i>	Notes
	<input type="checkbox"/>	<input type="checkbox"/>		
	<input type="checkbox"/>	<input type="checkbox"/>		
	<input type="checkbox"/>	<input type="checkbox"/>		
	<input type="checkbox"/>	<input type="checkbox"/>		

DRAWN	CHECKED	DATE	DWG.NO.
--------------	----------------	-------------	----------------

OP2008-MPH24D
 Do. #: M-13502

