

CERTIFIED FOR:	
JOB NAME	•
LOCATION	•
CUSTOMER	•
CUSTOMER P.O.	•

# Submittal Information: MPH-24D:24/9 Pedestal Hydrant

### **Composition:**



- Black painted cast aluminum Weather-Guard Dome Handle
- Available with Steel Grey Powder Coat finish or Grade 304 stainless steel shroud w/ seamlessly welded flange
- Male Hose Fitting / Vacuum Breaker

# **Mounting Hardware**

Black painted under-deck support flange w/ hardware

#### Features:

- The Auto-Drain port will discharge the water remaining in the standpipe to an open-site drain.
- The Hydrant utilizes a bronze full port auto drain ball valve within the shroud.
- The Under-deck Flange prevents the Hydrant from becoming dislodged from the roof membrane during operation.
- The Weather-Guard Domed Handle prevents moisture from entering the assembly when the valve is in the OFF position.
- Provided with "loose fit" wye strainer for field installation.

## **Options:**

Deck Cap – Suffix "D"

Suffix: xx/yy – Extended shroud for above or below roofline – 6" increments

## **Practical Application**

Where there is concern for potential damage to the hydrant assembly due to severe cold weather, the MPH-24D:24/9 Pedestal Hydrant with its Weather-Guard Dome provides a freeze proof hose station at required locations. The Auto-Drain port is located below the freeze line at the base of the hydrant. The Shroud and Base allow the contractor to make a positive, weather tight flashing to the hydrant in rooftop applications.

CERTIFICATION DATA								
QUANTITY Style Roof/Yard	•	Composition		Deck Cap	Extended Length (Max. 72")	Dimensions (Standard 24"	Notes	
	KOOI	Kooi/Taru		PC		(IVIUX. 72 )	above / 9" below)	

DRAWN	CHECKED	DATE	DWG.NO.

Doc. #: M-13502