Engineering Submittal Form

CERTIFIED FOR:			
Job Name		Customer Name	
Location		Customer P.O.	

Curbed Support Series: MX-1-(XXX)SA

Recommended Usage:

Single post pipe support models are designed specifically to comply with MSS SP-127-2001 Section 4.1c for the support of single pipes 4" IPS and smaller a maximum of 12" from bottom of pipe to roof deck. Accessory pipe clamp assemblies from ½" through 2" secured to 6" ATR are available for the MX-1.375-SA for use as condensate supports. Anchorage of equipment in seismic and high winds zones is a vital part of restraining rooftop piping systems. The MX-1.XXS-SA base may be used in conjunction with SCB-Seismic Cable Bracing as an attachment point for rooftop supports manufactured by MAPA Products. Multiple MX-1.XXX-SA units may be utilized for bridging systems and roof equipment curb applications.



MAPA Products Supports are designed and manufactured in accordance with MSS SP-58-2002 and MSS SP-69-2002.

Structural series supports are manufactured to conform also to MSS SP-127-2001.

Refer to MAPA Products "Recommended Installation Guidelines" for standard installation and spacing recommendations.

Base Model	**MX-1-375-SA** 3/8" ATR	**MX-1-500-SA** 1/2" ATR	**MX-1-700-SA** 3/4" ATR
Support Base:	18 gauge / grade 304 stainless Steel		
Base Dimensions	4" diameter X 6" H continuously welded to 10" flashing		
Recommended Weight Limit	75 lbs		
Under deck attachment hardware	14" ATR and 14 gauge 10" X 10" primed steel plate		
Features:	Grade 304 SS with continuously welded seams and rounded edges to prevent incidental damage to the roof surface and a 3" perimeter deck flange provides flashing to the roof deck.		
Optional Accessories	Provide as specified: Available with single post adjustable assemblies and Snap N Strut clamp sizes 12-16, 21-24, 25-29, 30-34, 35-38, 40-44,48-54, 56-63		

CERTIFICATION DATA				
QTY	**Base Model**	**Service**	**Size**	**Notes**

DRAWN	***CHECKED***	DATE	***DWG.NO.***

Doc. #: M-13701