



Engineering Submittal Form


CERTIFIED FOR:

Job Name:

Customer Name:

Location:

Customer P.O.:



MX-20SA18

Recommended Usage:

Use as a free standing; non-penetrating pipe support stand for all piping applications installed on single ply and built-up roofs within the recommended weight limit. This support is designed to accommodate single or multiple runs of conduit not exceeding weight load of 480lbs.

MAPA Products Supports are designed and manufactured in accordance with MSS SP-58-2002 and MSS SP-69-2002.

Refer to MAPA Products "Recommended Installation Guidelines" for standard installation and spacing recommendations.

Composition:

Strut Assembly	20" – 1 5/8" Aluminum Square Strut
Base	8" X 20" 304 SS
Threaded Rod Assembly	1/2" X 18" 304 SS ATR
Maximum Adjustability	4 1/2" to 18"
Footprint	160 sq in.
Weight Limit	480 lbs
Typical Pipe & Size	Single or Multiple EMT/Rigid Conduit

** When used for conduit; specific consideration should be given to the size and number of conduits and the supports recommended weight limit so that maximum support load is not exceeded.*

Optional Accessories:

- MWP 1224 – 9.2mm thick rubber walk pad.
- Snap-N-Strut Clamps (Refer to SNS selection chart for sizing)

Certification Data

Support Pad Options							
QTY	NP	P	WP	Pipe Strap	Pipe Size	Service	Notes & Options
	<input type="checkbox"/>	NA	<input type="checkbox"/>	<input type="checkbox"/>			
	<input type="checkbox"/>	NA	<input type="checkbox"/>	<input type="checkbox"/>			

Doc. #: M-13825